



# 4MP WDR Vari-focal Day/Night Box Network Camera



FCS-1155

H/W Version: 2

## Key Features

- 1/3" Progressive Scan CMOS Sensor
- Auto Back Focus
- CS Mount Lens Socket. (*Lens are not included*)
- Up to 4 megapixel resolution 2688x1512 pixel
- 120dB WDR
- Automatic Day/Night Operation
- Built-in Micro SD/SDHC/SDXC card slot, up to 128 GB
- Audio and Alarm I/O, RS-485 for P/T Housing, BNC for Analog Video output
- PoE(802.3af), DC12V, DC24V, AC24V
- Support Quad Stream H.264, MPEG4, MJPEG

## Technical Specification

<b>CAMERA</b>	
Image Sensor	1/3" Progressive CMOS Sensor
Minimum Illumination	<ul style="list-style-type: none"><li>• Color: 0.1 lux</li><li>• Black and White: 0.01 lux</li></ul>
Shutter Speed	1 ~ 1/10,000 sec
Signal/Noise Ratio	> 50dB
Lens	CS Mount ( <i>Lens not included</i> )
Day and Night	Automatic IR Cut Filter (ICR)
Dynamic Range	Wide Dynamic Range (WDR) 120dB
<b>COMPRESSION</b>	
Video CODEC	H.264 (ONVIF Main Profile), MPEG4, MJPEG
Video Bit Rate	Variable or Constant Mode
Audio CODEC	G.711, G.726, AAC, LPCM

<b>IMAGE</b>	
Max Resolution	2688 x 1512
Frame Rate	<ul style="list-style-type: none"> <li>• 15 fps at 2688x1512, 2560x1440</li> <li>• 30 fps at 2304x1296, 1920x1080, 1280x1024</li> <li>• 60 fps at 1280x720, 1024x768, 800x600</li> </ul>
Image Enhancement	<ul style="list-style-type: none"> <li>• AGC/AWB/AES</li> <li>• Privacy Masks (up to 5 zones)</li> <li>• Back Light Compensation (BLC)</li> <li>• 2D/3D/Color Digital Noise Reduction</li> </ul>
<b>NETWORK</b>	
Storage	<ul style="list-style-type: none"> <li>• Built-in Micro SD/SDHC/SDXC card slot, up to 64 GB</li> </ul>
Alarm Trigger	<ul style="list-style-type: none"> <li>• Motion Detection (up to 10 zones)</li> <li>• Tamper Alarm</li> <li>• 1 x Digital Input</li> <li>• 1 x Digital Output</li> </ul>
Protocol	TCP, UDP, HTTP, HTTPS, DHCP, PPPoE, RTP, RTSP, IPv4, IPv6, DNS, DDNS, NTP, ICMP, ARP, IGMP, SMTP, FTP, UPnP, SNMP, QoS
Security	<ul style="list-style-type: none"> <li>• User Login Authentication (DIGEST, SSL)</li> <li>• User Access Level (Administrators, and Users)</li> <li>• IP Filtering</li> <li>• IEEE802.1x</li> </ul>
Standard	<ul style="list-style-type: none"> <li>• ONVIF</li> </ul>
<b>ENVIRONMENTAL</b>	
Interface	<ul style="list-style-type: none"> <li>• 1 x RJ45 10/100 Ethernet (100Base-T) interface</li> <li>• 1 x RS-485</li> <li>• BNC (Analog Video)</li> </ul>
Power Supply	PoE (IEEE802.3af), DC12V, DC24V, AC24V
Power Consumption	4W Max
Operating Temperature	-20°C to 55°C
Relative Humidity	Up to 90% non-condensing
Dimension	125 x 82 x 52 mm (WxDxH) without lens
<b>REGULATORY APPROVALS</b>	
Standards	<ul style="list-style-type: none"> <li>• FCC</li> <li>• CE</li> <li>• RoHS</li> <li>• Manufactured in ISO9001 and ISO14001-certified factory</li> </ul>

## Order Information

<b>FCS-1155</b>	3MP WDR Vari-focal Day/Night Box Network Camera
<b>CAS-1402</b>	3-10.5mm Vari-focal Day/Night 3-Megapixel Lens P-Iris