



one world_one brand_one level_

LevelOne Pocket Print Server



T E C H N I C A L D A T A

Standard Conformance:

- Ethernet II, IEEE802.3, IEEE802.2 SNAP

Physical Port

- LAN Port: 10BaseT (STP) (FPS-3001TU)
10/100 Base T (STP) (FPS-3001TXU)
- Printer Port: DB 36

Protocol:

- IPX/SPX, TCP/IP
- PTP over TCP/IP, PTP over NetBEUI
- Apple EtherTalk, SMB over NetBEUI

Network Environment

- Windows 95/98/NT/2000/XP
- MAC
- Unix
- NetWare NDS & Bindery

Management:

- WebAdmin Management (FPS-3001TXU)
- BiAdmin Management
- NWAdmin Management
- HP's JetAdmin (FPS-3001TXU)
- SNMP Management (FPS-3001TXU)

Special Features

- Internet Printing (proprietary)
- IPP (Internet Printing Protocol) (FPS-3001TXU)
- Bidirectional IEEE 1284
- Printing ECP Mode (FPS-3001TXU)

Printing

- EPS-3001TX up to 200k printing throughput
- EPS-3001TXU up to 650k printing throughput
- EPS-3001TX: 200KB Memory
- EPS-3001TX: 650KB Memory
- Logical Printer: 3

Physical characteristics:

- Dimension: 59,7mm (W) x 57mm (D) x 20mm (H)
- Operating Temperature: 0°C to 40°C
- Storage Temperature: -10°C to 70°C
- Shipping Temperature: -40°C to 70°C
- Operating Humidity: 10 ~ 80%
- Storage Humidity: 5 ~ 80%
- Shipping Humidity: 5 ~ 100%

Certification:

- FCC Part 15
- CE

Ordering Information:

- EPS-3001TU 1 Port 10Mbps
Printer Server
- EPS-3001TXU 1 Port 10/100Mbps
Printer Server