# Datasheet\_FBR-1403TX



one world\_one brand\_one level\_

# LevelOne Router

LevelOne ADSL Router 4 Port LAN with Printer Server



#### ECHNICAL

# **Standard Conformance:**

■ IEEE 802.3 and IEEE 802.3u

### **Physical Port**

- WAN Port: 10/100BaseT Mbps (RJ45)
- LAN Port: 10/100BaseT auto sensing (RJ45), 1 x uplink port
- LAN-WAN (ADSL/Cable Modem): 10 Mbps
- Switch Built-in: 4 Ports
- Printer Port: D-Sub 25

#### Internet Access Sharing

- Dial-on-demand, Auto Disconnect
- Login: PPPoE, PPTP
- Authentication: PAP, CHAP
- Protocol: NAT, HTTP, DHCP, TCP/IP, UDP, PAP, CHAP, RIP1, DDNS, UPnP
- DHCP Server/Client support
- Max simultaneous Internet access users: 253

#### **Physical Characteristics:**

- Dimension: 241mm (W) x 150mm (D) x 27mm (H)
- Operating Temperature: 0°C to 40°C
- Storage Temperature: -10°C to 70°C

#### LEDs:

■ Power, Status, 4 x LAN Link/Act, 4 x LAN 100 Mbps, WAN Status, Printer Act and Err

#### **Printer Sharing**

- LPD/LPR Printing
- Peer to Peer Printing over TCP/IP

#### Management:

- Web Browser Management
- Remote Management

#### Firewall:

- Built in NAT/NATP firewall
- Attack Alert (Email) log
- Stateful Inspection firewall for DoS (Denial of Service) Attacks
- URL Filter
- Access Control by Group
- Local Password
- VPN (pass thru) : PPTP, Ipsec, L2TP
- Special Application support
- DMZ, Dynamic DNS, Virtual Server support

## **Power Requirement**

12V/1,5mA DC External

#### Router

- Cross Segment Static Route
- RIP1 support
- LAN to LAN Connectivity (Bridging)

#### Certification:

- FCC Part 15
- CE

#### **Ordering Information:**

■ FBR-1403TX ADSL Router 4 Ports LAN

with Printer Server

