

LevelOne Broadband Router with print server

LevelOne Broadband Router with print server

TECHNICAL DATA

Standard Conformance:

- IEEE802.3,IEEE802.3u,IEEE802.3x

Ports:

- LAN Port 4 x RJ45,10/100 Mbps with Auto-MDI/MDIX
- WAN Port 1 x RJ45,10/100 Mbps with Auto-MDI/MDIX
- Parallel Port 1 x IEEE 1284 Interface

General Protocols:

- IP Protocol:TCP/IP v4,DHCP server,Proxy DNS Server
- User Interface:Web-Based
- Management:Web-Based,SNMP

WAN Type:

- Static IP,dynamic IP
- PPP over Ethernet
- PPTP,L2PT
- Telstra BigPond

Firewall:

- NAT firewall and SPI firewall
- DoS Detection
- Max.253 User
- Up to 20 Virtual Server
- Up to 8 Special Applications
- Up to 5 DMZ Host (Virtual Computer)

Access Control:

- MAC-level Access Control
- Inbound/Outbound Packet Filter
- Domain Access Control
- URL Blocking

Event Logging:

- On-web logging
- Syslog supported
- Email Alert

Other Features:

- Dynamic DNS:DynDns.org (dynamic/static), TZO.org,dhs.org
- Up to 8 Routing entries
- Schedule Rules
- Configuration Backup

Input Power:

- DC 5V/2A external power supply

Physical Characteristics:

- Dimensions:220mm (B) x 130mm (T) x 32mm (H)
- Weight :555g
- Operating Temperature Temperature:0~40oC, Humidity 10%~90% non-condensing
- Storage Temperature Temperature:-20~70oC, Humidity:0~95% non-condensing

Certification and Reliability:

- FCC,CE,VCCI,UL
- Reliability Stress Test; Vibration Test; Drop Test

Ordering Information:

- FBR-1412 Broadband Router with print server