



PoE IP Network Camera w/ 2-way Audio



FCS-1081A

H/W Version: 1

Product Overview

The LevelOne FCS-1081A PoE IP Camera is an easy to deploy Network Camera within a PoE LAN. It is suitable for indoor deployment as well as outdoor deployment when used with the BOH-1000/1100/1300 Box-type Outdoor Housing.

Camera Features

The FCS-1081A makes use of a 1/3"-inch Color CCD sensor for capturing clear imagery. The camera also features a 10x digital zoom and supports resolutions of up to 704x480 pixels at maximum 30 frames per second. It also supports selectable MPEG4 or MJPEG compression modes.

Different Accessories for Different Needs

The FCS-1081A as standard IP Camera has a changeable 4mm CS-mount lens. Available as

accessories, LevelOne offers the CAS-1000A with a 3.5 ~ 8mm lens and the CAS-1100 with a 6 ~ 60mm lens.

For outdoor deployment the PoE IP Camera can be housed inside the IP66 rated BOH-1000/1100/1300 Outdoor Housing.

Free Bundled Software

The free bundled 32-channel software package, IP CamSecure 32 Lite, allows for simultaneous monitoring of IP Cameras. Other features include automatic snapshot, recording of streaming video, motion detection and a 60sec. pre/post event buffer.

LevelOne further has available alternative Digital Surveillance software packages for professional and advanced use.



Key Features

- Supports Power over Ethernet (IEEE802.3af) standard
- Selectable MJPEG/MPEG4 compression
- CS-mount lens changeable with different lens specifications
- Includes a free 4mm lens
- Two-way audio supported
- Provides BNC video output for CCTV system
- Full D1 resolution at 30/25 frames per second
- Features controllable auto-iris, backlight compensation and auto electronic shutter
- Supports UPnP, DDNS, motion detection, and alarm snapshot

Works Well With



FCS-9464
IP CamSecure Pro64 Mega



FCS-7011
1-port PoE Video Server

Technical Specification

Network

1 x RJ-45 10/100 Mbps port
PoE(Power over Ethernet) (IEEE802.3af) compliant

Video

Compression Mode

MPEG4/MJPEG simultaneously

Max. Resolution

704x480 pixels at 30 fps (NTSC)
704x576 pixels at 25 fps (PAL)

Frame Rate

704 x 480 pixels @30fps (NTCS)
704 x 576 pixels @25fps (PAL)
320 x 240 pixels @30fps (NTCS)
320 x 240 pixels @25fps (PAL)
160 x 120 pixels @30fps (NTCS)
160 x 120 pixels @25fps (PAL)

Still Picture

JPEG

Video Record

AVI

Camera

Sensor

1/3" Color CCD sensor

Lens

4mm

View Angle

Vertical 53.4°
Horizontal 70.7°

Minimum Illumination

0.05Lux/F1.2

Electronic Shutter (Sec)

1/60 ~ 1/100,000 sec

AGC/AWB/AES/BLC

Video-drive/DC-drive Iris Control

Audio

Audio In/Out

External microphone input jack
External speaker output jack

Audio Codec

G.711 PCM 64 kbits

S/N Ratio

48db

Zoom

Digital Zoom

10x

Hardware & Environment

Flash ROM

8MB Flash ROM

SDRAM

32MB SDRAM

Housing

Indoor use
BOH-1000/BOH-1100/BOH-1300 optional for IP66-rated outdoor use

Power

Power adapter is not included.
POW-1201,12V/1.25A power adapter, optional

Temperature

Operating: 0°C ~ 50°C

Dimension

157X60X50mm

Weight

346.8g

Supported Protocols

IPv4,TCP/IP, HTTP, HTTPS, UPnP, RTSP/RTP/RTCP, IGMP, SMTP, FTP, DHCP, NTP, DNS, DDNS and PPPoE

Software

Bundled with 32-Channel LevelOne IP CamSecure Lite surveillance management software

Viewing System Requirement

OS

Microsoft Windows 2000/XP/Vista

Browser

IE 6.x or above


3GPP Player

Real Player 10.5 or above
Quick Time 6.5 or above

EMI and Safety

FCC, CE

Product Diagram



Order Information

FCS-1081A: PoE IP Network Camera w/ 2-way Audio (*Power supply is excluded)

Package Content

FCS-1081A, 4mm Fixed Lens, Camera Stand, CD Manual/Utility, Quick Installation Guide

Optional Accessories



BOH-1000
Outdoor Housing for
Box Cameras (24VAC)



BOH-1100
Outdoor Housing for
Box Cameras (12VDC)



BOH-1300
Outdoor Housing for
Box Cameras
(12VDC/24VAC)



CAS-1000A
3.5~8mm Vari-Focal
Lens



CAS-1100
6~60mm Vari-focal Lens



POW-1201
12V/1.25A Switching
Power Adapter

All mentioned brand names are registered trademarks and property of their owners. Technical specifications are subject to change without notice.

© Copyright Digital Data Communications GmbH. All Rights Reserved.