



Day/Night Speed Dome Pro Network Camera



FCS-4010

H/W Version: 1

Ultimate Surveillance Technology

LevelOne's FCS-4010 is powerful pan/tilt/zoom speed dome network camera. With 18x optical zoom, it's easy to focus and target objects within sight. The progressive scan Sony CCD sensor captures crystal clear images with no jagged edges, even when observing fast moving objects.


Day and Night and Vandalproof

With a removable IR-cut filter, the FCS-4010 offers the highest level of surveillance, providing vivid images without any distortion in the daytime. When lighting conditions turn

poor the IR-cut filter is removed, adding a dramatic improvement to image quality. And with an outdoor IP-66 rated vandalproof dome, this camera withstands severe weather and any forceful blows or attempts at destruction.

Where to use?

As a feature-rich camera loaded with functionality, this camera is ideal for use in airports, freeway surveillance, parking lots and garages, as well as shopping malls. When you require the highest levels of security but want a simple to install and use network camera, FCS-4010 is the right choice for you.



1. General I/O terminal block
2. Ethernet 10/100 RJ45 plug
3. Audio out (green)
4. Microphone in (pink)
5. Power cord socket (black)
6. Earth

Key Features

- 1/4" progressive CCD sensor for capturing fast-moving objects without jagged edges
- Supports 18x Optical and 4x Digital zoom
- Dual MPEG4/MJPEG compression mode
- Auto-removable IR-cut filter for Day/Night viewing
- Extended I/O for sensor & alarm
- Two-way audio
- Vandal-proof and Waterproof IP66 rated for indoor/outdoor deployment
- Supports 360° pan and 90° tilt, continuous rotation
- Free software included (Industry-leading 32-channel IP CamSecure Lite™ software)

Works Well With



FCS-9464
IP CamSecure Pro64 Mega




CAS-4200
USB Joystick for PTZ Network Cameras

Technical Specification

| |
|--|
| Network |
| 1 x RJ-45 10/100 Mbps port |
| Video |
| Compression Mode |
| MPEG4/MJPEG |
| Max. Resolution |
| 640x480 pixels at 30/25 fps |
| Frame Rate |
| Up to 30/25 frames at 176x144 |
| Up to 30/25 frames at 320x240 |
| Up to 30/25 frames at 640x480 |
| Still Picture |
| JPEG |
| Video Record |
| .MP4 |
| Camera |
| Sensor |
| 1/4" SONY progressive CCD sensor |
| Lens |
| 4.1~73.8mm/F1.4~3.0 |
| View Angle |
| Vertical 2.1°~36.5° |
| Horizontal 2.8°~47.4° |
| Minimum Illumination |
| 1.61Lux (F1.4, 1/30s) |
| 0.38Lux (F1.4, 1/30s, without IR cut filter) |
| Infrared Facility |
| Removable IR cut filter |
| Electronic Shutter (Sec) |
| 1/2 ~ 1/10,000 sec |
| AGC/AWB/AES/BLC |
| Auto Iris Control |
| Audio |
| Audio In/Out |
| External microphone input jack |
| External speaker output jack |
| Audio Codec |
| GSM-AMR |
| MPEG-4 AAC |
| Supports two-way audio by SIP protocol |
| S/N Ratio |
| More than 50dB |
| PTZ |
| PT |
| Pan 360° continue |
| Manual Pan Speed 0.1~300°/Sec |
| Tilt 0°~90° |
| Manual Tilt Speed 0.1~120°/Sec |
| Preset Speed 400°/Sec |
| Preset Accuracy ±0.25° |
| Number of preset positions |
| 128 |
| Zoom |
| Optical: 18x |
| Digital: 4x |

| |
|--|
| Hardware & Environment |
| Flash ROM |
| 8MB Flash ROM |
| SDRAM |
| 64MB SDRAM |
| Housing |
| Indoor/Outdoor use |
| IP66 water-proof |
| Vandal-proof |
| Day/Night |
| Removable IR cut filter |
| Digital I/O |
| 1xIn, 1xOut |
| Power |
| 24VAC 2A 60/50Hz |
| Temperature |
| Operating: -20°C ~ 60°C |
| Humidity |
| Operating: 20%~80% RH |
| Dimension |
| φ200mm x 270mm (H) |
| Weight |
| 3740g |
| Supported Protocols |
| IPv4, TCP/IP, HTTP, HTTPS, UPnP, RTSP/RTP/RTCP, GMP, SMTP, FTP, DHCP, NTP, DNS, DDNS and PPPoE |
| Software |
| Bundled with 32-Channel LevelOne IP CamSecure Lite surveillance management software |
| Viewing System Requirement |
| OS |
| Microsoft Windows 2000/XP/Vista |
| Browser |
| Mozilla, Firefox, Safari, Netscape, IE 6.x or above |
| 3GPP Player |
| Real Player 10.5 or above |
| Quick Time 6.5 or above |
| EMI and Safety |
| FCC, CE |

Product Diagram



Order Information Package Content

FCS-4010: Day/Night Speed Dome Pro Network Camera

FCS-4010
Power Adapter
Wall Mount Bracket
Dome Cover
Inner Cover
Silica Gel
Metal Ring
Screw kit
Alignment Sticker
RJ45 Female/Female Coupler
CD Manual/Utility
Quick Installation Guide

Optional Accessories



CAS-4200
USB Joystick for PTZ
Network Cameras



CAS-3015
IR Illuminator (15M)



CAS-3030
IR Illuminator (30M)

All mentioned brand names are registered trademarks and property of their owners. Technical specifications are subject to change without notice.

© Copyright 2008 Digital Data Communications GmbH. All Rights Reserved.