

### IP Network Camera w/ Infrared LEDs

#### Product Overview

The LevelOne FCS-5030 is a camera with crystal LEDs mounted around the lens for night viewing. It features a Sony CCD color sensor for clear picture quality. The camera is housed in an IP66 rated housing and is suitable for both indoor and outdoor surveillance.

#### Fast Ethernet Video Surveillance

The FCS-5030 Network Camera supports 10/100Mbps network connectivity for easy installation. It provides a RJ-45 port for quick connectivity with a network switch or router. It supports MPEG-4 and MJPEG dual-streaming image compression.

#### Day and Night Viewing

The FCS-5030 features an 8mm fixed lens and a 1/3" color Sony CCD image sensor to capture imagery at full D1 resolution at 25/30 frames per second. It allows for color image capturing under normal light conditions and black and white imagery under low light conditions. When operating at night time, with the assistance of the crystal LED's, the FCS-5030 has a 30 meter image capturing range, making it a suitable product for high-end surveillance applications.

#### Bundled LevelOne IP CamSecure Lite and Windows

The FCS-5030 IP Network Camera is bundled with LevelOne IP CamSecure Lite. It is an easy to use surveillance management tool that allows users to monitor the camera locally over the LAN or remotely over the Internet.



**FCS-5030**

### Key Features

- Professional Day/Night network camera with 12 pcs infrared LEDs.
- Features a Sony CCD Sensor capturing 25/30 frames per second imagery in full D1 resolution
- IP-66 waterproof housing for outdoor use
- Supports MJPEG and MPEG-4 dual-streaming video compression
- Features Motion Detection and Event-notification via E-mail or FTP
- Two-way audio
- Extended digital I/O for sensor and alarm
- Remote viewing over the Internet or via 3G Mobile phone
- Bundled with LevelOne IP CamSecure Lite surveillance management software

### Technical Specification

#### Video

##### Image Sensor

1/3" Color Sony CCD

##### Lens

8mm, F2.0 Fixed Focus  
0Lux/F2.0 when IR on

##### IR LEDs

12 crystal IR LEDs for night view up to 30m

##### Compression

MPEG-4/MJPEG Dual Stream

##### Resolution Support

NTSC: 704x480, 352x240, 176x120@30 frames per second  
PAL: 704x576, 352x288, 176x144 @25 frames per second

##### Video Options

Adjustable image size  
Picture quality  
Adjustable Bit-rate  
Motion-Detection  
Time Stamp  
Text Overlay

#### Audio Specifications

##### Compression

AAC, GSM-AMR

##### Microphone/Speaker

Line In/Audio Out

#### Software Specifications

##### Bundled with LevelOne IP CamSecure Lite

32-Channel monitoring and recording software

#### Power Adapter

12V/1.5A

#### Hardware Specifications

##### Onboard Memory

RAM: 64MB SDRAM

ROM: 8MB FLASH ROM

##### LAN

RJ-45 Ethernet 10/100Mbps BaseT

##### Digital Input/Output Connector

1x In, 1x Out

##### Supported Protocols

TCP/IP, SMTP, HTTP, FTP, DDNS, Telnet, DNS, DHCP, NTP, RTSP/RTP, UPnP

##### Operating Parameters

Temperature: -20°C~50°C

Humidity: 95% RH

##### Dimensions

158mm (L) x 105mm (W) x 108mm (H)

##### Weight

1010g

##### Certification

CE, FCC

#### System Requirements

##### Operating System

Microsoft Windows 2000/XP/VISTA

##### Web Browser


Internet Explorer 6.x or above

FireFox 1.5.0.x or above

#### Package Contents

- FCS-5030
- Power Adapter
- Camera Stand
- Installation CD
- Quick Installation Guide

### Product Diagram



### Order Information

**FCS-5030:** IP Network Camera w/ Infrared LEDs