



## 5-Port Fast Ethernet Switch



FEU-0510

H/W Version: 1

### Product Overview

The LevelOne FEU-0510 is a 10/100Mbps NWay Unmanaged Switch with outstanding performance and high efficiency. With 5 NWay auto-negotiation ports, this switch fulfills the needs of connecting users on a network with automatic selection of best network speed and duplex mode.

### Power Saving Features

The FEU-0510 supports Green Ethernet to provide power-saving benefits without compromising performance. One way is to automatically detecting the length of connected cables and to adjust power usage by saving energy on shorter cable connections.

### Get Optimal Bandwidth for Media Traffic through VIP Ports

The FEU-0510 is designed with two port-based QoS ports which provide considerably enhanced bandwidth quality. Users on the two QoS ports can experience better performance for internet surfing, online gaming and multimedia streaming through prioritized bandwidth settings.

### Easy to Use

The FEU-0510 is plug-and-play and supports all kind of network protocols to make installation and network management easy and fast. LED indicators provide a quick and easy way to read port and switch information.



1. LED Indicators
2. 10/100Mbps RJ-45 Ports
3. QoS Port
4. Power Socket

### Key Features

- 5 x 10/100Mbps RJ-45 NWay Ports
- Supports NWay protocol for speed (10/100Mbps) and duplex mode (half/full) detection
- Supports MDI/MDI-X auto crossover and support full/half duplex operation on all ports
- Supports back-pressure (half duplex) and flow control (IEEE 802.3x)
- Wire-speed packet filtering and forwarding rate
- Store-and-forward architecture filters fragment & CRC error packets
- Desktop size design for easy deployment
- Metal casing with internal power supply
- Support two Port-based QoS (Quality of Service) ports.

### Works Well With



**FNS-1020**  
1-Bay Simple Network Storage



**FBR-1161**  
ADSL2+ Modem Router

## Technical Specifications

### Standard

IEEE802.3 (10BASE-T)  
IEEE802.3u(100BASE-T)  
IEEE802.3x Flow Control

### Interface

5 x 10/100Mbps NWay RJ45 ports

### NWay Protocol Support

Network speed: 10/100 Mbps  
Duplex mode: Full and Half

### MAC Address Table

2K

### Buffer Memory

48KB

### Filtering/Forwarding Rate

10Mbps: 14,880pps/14,880pps  
100Mbps: 148,800pps/148,800pps

### LED indicators

System: Power  
Port: Link/Act

### Power Supply

Internal power 100~240V AC, 50~60 Hz

### Operating Temperature

0°- 40°C (32°- 104°F)

### Operating Humidity

10% ~ 90% (non-condensing)

### Dimensions (L x W x H)

150 x 85 x 26mm


### Case Material

Metal

### Emission

FCC/CE/VCCI Class B

## Product Diagram



## Order Information

### FEU-0510: 5-Port Fast Ethernet Switch

## Package Contents

FEU-0510  
Power Cord  
Rubber Feet x 4  
QIG Manual