



one world_one brand_one level_

LevelOne ServCon

LevelOne 4 Bay Gigabit Rack-Mounted NAS



TECHNICAL DATA

Maximum HDDs

- 4 Drive Trays for 3.5" IDE HDDs supporting Hot Swap & Hot Spare

Network Port

- one 10/100/1000Mbps Ethernet Port

Port for UPS

- one RS-232 Port specifically Supports
- APC Smart UPS 700
- Phoenixtec A1000

Port for Tape Drive

- one Ultra-160 SCSI Port specially Supports
- IBM Tape Drive Model 440 – (DLT Cartridge Tape)
- Tandberg DLT 7000 (Quantum compatible) – (DLT Cartridge Tape)
- Exabyte Mammoth-LT – (8mm Data Cartridge Tape)
- HP SureStore DDS4 DAT Tape Drive – (DDS Cartridge Tape)

Network

- Transport Protocols: TCP/IP, NetBEUI, IPX, Apple Talk
- File Protocols: Microsoft Windows (CIFS/SMB), Apple (AFP), Unix (NFS), Novell NetWare, Internet (Web Browser), FTP
- Network Client Types: Microsoft Windows 95/98/ME/NT 4.0/2000/XP, MAC OS 7.5+, Linux/Unix, NetWare

Management

- Web-based GUI
- SNMP
- Remote Shutdown/Reboot

Security

- SNMP Notification, e-Mail Alerts and Audio Buzzer
- Logs of active Users, Events and DHCP

System

- OS: Embedded Linux O.S., merely compact Size of 9MB
- CPU: Intel Celeron 850MHz CPU, 256MB RAM
- O.S. stored in Flash/DoM (Disk on Module)
- Multi-Language Supports

LEDs

- Power, Error, Network, Disk

LCD Panel

- Displays HDD Numbers/Volume, Server Name, IP, Date/Time, Power Status, Network Setting, CPU Temperature Monitor

Raid Support

- Raid 0 (Disk Stripping)
- Raid 1 (Disk Mirroring)
- Raid 5 (Disk Stripping with Parity)
- Hot Spare

Physical Characteristics

- Power: 100 - 240V, Redundant & Hot Swappable ATX Power Supply
- Operating Temperature: 0°C to 45°C
- Dimensions: 430mm x 570mm x 44mm (L x W x H)

Regulation

- CE, TUV, FCC, UL

Ordering Information

- GNS-8000 4 Bay Gigabit Rack-Mounted NAS