



LevelOne ProCon 19" Gigabit Web Smart Switch

LevelOne ProCon 19" Gigabit Web Smart Switch

T E C H N I C A L D A T A

Standard Conformance:

- IEEE 802.3 10BASE-T Ethernet
- IEEE 802.3u 100BASE-TX Fast Ethernet
- IEEE 802.3ab 1000BASE-T Gigabit Ethernet
- IEEE 802.3x Full Duplex Flow Control

Number of Ports:

- 16/24 x 10/100/1000Mbps Auto-MDIX RJ-45 ports
- 2 x Mini GBIC ports

Data Transfer Rate:

- Ethernet: 10Mbps (half duplex), 20 Mbps (full duplex)
- Fast Ethernet: 100Mbps (half duplex), 200Mbps (full duplex)
- Gigabit Ethernet: 2000Mbps (full-duplex)Built-in

Network Cables:

- 10BASE T: 2-pair UTP Cat. 3, 4, 5; up to 100m
- 100BASE-TX: 2-pair UTP Cat. 5; up to 100m
- 1000BASE-T: 4-pair UTP Cat. 5; up to 100m

Transmit Methods:

- Store-and-Forward

Operational Features:

- Up to 4K/8K for GSW-1675T/2475T uni-cast addresses entities per device, self-learning, and table aging
- Supports IEEE802.3x flow control for full-duplex mode ports
- Supports port-base VLAN and QoS
- Supports Trunking
- Supports Port-mirroring
- Supports Port-setting for Speed/Disable, Flow control
- Friendly Web Management Interface
- Standard 19" rack-mount size

Power Requirements:

- Power input 100-240V AC, 50/60 Hz internal universal power supply
- Power consumption 25W (Max) for GSW-1675T; 32W (Max) for GSW-2475T

Physical Characteristics:

- Temperature: Operating: 0° ~ 40° C; Storage: -10° ~ 70° C
- Humidity: Operating: 10% ~ 90%
- Dimension 440mm(W) * 210mm(D) * 40mm(H)

EMI and Safety:

- CE

Ordering Information:

- GSW-1675T: 19" Gigabit Web Smart Switch (16*1000 + 2 Mini GBIC)
- GSW-2475T: 19" Gigabit Web Smart Switch (24*1000 + 2 Mini GBIC)