



IES-0822

4 x 802.3af + 3 FE+ 1 MM SC Unmanaged Switch

-40 to 75C, DIN-rail

Overview

LevelOne IES-0822 Industry Ethernet Switch provides 4 PoE ports of 10/100Base-TX plus 3 ports of 10/100Base-TX Ethernet plus 1 port 100FX Multimode SC fiber to enable high speed network at mission-critical environment. This device is designed to be mounted on an industry standard DIN-rail, plus the clearly visible status LEDs provide simple monitoring of port link activity.

High Reliability

All components are built to withstand harsh environment applications without compromise where humidity, temperature variation and even shock vibration are concerns, including Electric & Utility, Critical Infrastructure, Transportation and Surveillance Security. This device operates under -40 to 75 Celsius (-40 to 167 Fahrenheit) temperature.

Power over Ethernet

This switch is Power Sourcing Equipment (PSE), and it is fully complied with IEEE 802.3af PoE standard at maximum 15.4W power budget per port. It helps to save infrastructure wiring costs dramatically by eliminating electric wiring and less UPS needed.

Features

- Provides flexibility of 8 Ethernet ports that configure in combinations of copper and fiber optic interfaces
- -40°C to 75°C (-40°F to 167°F) and is tested for functional operation @ -40°C to 85°C (-40°F to 185°F)
- Port1 - 4 support IEEE802.3af Power over Ethernet (PoE) Power Sourcing Equipment (PSE)
- Provides DIN-rail, panel or rack mounting

Redundancy

This redundant power system is designed to meet the challenge of power failure to ensure reliability and constant availability. Single power design works fine in non-critical network applications, but it falls short drastically for network applications in transportation, automate production or banking.

Plug & Play

This unmanaged Industrial Ethernet Switch is designed for the demanding industrial environments at businesses in need of instant connectivity with no setup or configure required, truly plug and play.


Safety

This device has been tested under UL508 standard for Industrial Control Equipment to endurance under test turn on and off 6,000 times while loaded, with no single failure. Plus, it is the E-Mark complied to ensure reliability at rolling stock applications. It's highly reliability and safety measurement to ensure field hardened, especially for the harsh environment.

- Alarms for power and port link failure by relay output
- Redundant power inputs with Terminal Block and DC Jack
- Complies with IEC61000-6-2 EMC Generic standard immunity for Industrial environment
- Complies with NEMA TS2 Environmental requirements for Traffic control equipment
- 10/100Mbps-Full/Half-duplex, Auto-Negotiation, Auto-MDI/MDIX

Diagrams

Unit: mm



Specifications

Technology	
Standards	<ul style="list-style-type: none"> IEEE802.3 10BASE-T, IEEE802.3u 100BASE-TX/FX, IEEE802.3x, IEEE802.3af
Forward and Filtering Rate	<ul style="list-style-type: none"> 14,880pps for 10Mbps 148,810pps for 100Mbps
Packet Buffer Memory	<ul style="list-style-type: none"> 1M bits
Processing Type	<ul style="list-style-type: none"> Store-and-Forward Half-duplex back-pressure and IEEE802.3x full-duplex flow control
Address Table Size	<ul style="list-style-type: none"> 1024 MAC addresses

Power	
Power Input	<ul style="list-style-type: none"> Redundant power inputs: Terminal Block: 47 - 55VDC DC Jack: 47 - 55VDC
Power Consumption	<ul style="list-style-type: none"> Device: Max. 10W (without PoE) PoE power budget (depends on power input): 61.6W Max.
PoE Power Output	<ul style="list-style-type: none"> Port 1 to 4 IEEE802.3af: up to 15.4W/port, 47 - 55VDC, 350mA Max
<ul style="list-style-type: none"> Supports overload current protection Supports reverse polarity protection 	

Mechanical	
Casing	<ul style="list-style-type: none"> Aluminum case IP30
Dimensions	<ul style="list-style-type: none"> 68mm (W) x 110mm (D) x 135mm (H) (2.68" (W) x 4.33" (D) x 5.31" (H))
Weight	<ul style="list-style-type: none"> 1Kg (2.2lbs.)
Installation	<ul style="list-style-type: none"> DIN-Rail (Top hat type 35mm), Panel, Rack Mounting

Interface	
Ethernet Port	<ul style="list-style-type: none"> 10/100BASE-TX: 8, 7 or 6 ports 100BASE-FX: 0, 1 or 2 ports
LED Indicators	<ul style="list-style-type: none"> Per Unit: Power Status (Power 1, Power 2, Power 3) Per Port: 10/100TX, 100FX: Link/Activity
Alarm Contact	<ul style="list-style-type: none"> One relay output with current 1A @ 24VDC

Environment	
Operating Temperature	<ul style="list-style-type: none"> -40°C to 75°C (-40°F to 167°F) Tested @ -40°C to 85°C (-40°F to 185°F)
Storage Temperature	<ul style="list-style-type: none"> -40°C to 85°C (-40°F to 185°F)
Ambient Relative Humidity	<ul style="list-style-type: none"> 5% to 95% (non-condensing)
MTBF	<ul style="list-style-type: none"> 29.38 years

Regulatory Approvals	
ISO	<ul style="list-style-type: none"> Manufactured in an ISO9001 facility
Safety	<ul style="list-style-type: none"> UL508 (Pending)
EMI	<ul style="list-style-type: none"> FCC Part 15, Class A, VCCI EN55022, EN61000-3-2, EN61000-3-3
EMS	<ul style="list-style-type: none"> EN61000-6-2 <ul style="list-style-type: none"> EN61000-4-2 (ESD Standards) Contact: + / - 4KV; Criteria B Air: + / - 8KV; Criteria B EN61000-4-3 (Radiated RFI Standards) 10V/m, 80 to 1000MHz; 80% AM Criteria A 3V/m, 1400 to 2000MHz; 80% AM Criteria A 1V/m, 2000 to 2700MHz; 80% AM Criteria A EN61000-4-4 (Burst Standards) Signal Ports: + / - 4KV; Criteria B D.C. Power Ports: + / - 4KV; Criteria B EN61000-4-5 (Surge Standards) Signal Ports: + / - 1KV; Line-to-Line; Criteria B D.C. Power Ports: + / - 0.5KV; Line-to-Earth; Criteria B EN61000-4-6 (Induced RFI Standards) Signal Ports: 10Vrms @ 0.15 - 80MHz; 80% AM Criteria A D.C. Power Ports: 10Vrms @ 0.15 - 80MHz; 80% AM Criteria A EN61000-4-8 (Magnetic Field Standards) 30A/m @ 50, 60Hz; Criteria A
Environmental Test Compliance	<ul style="list-style-type: none"> IEC60068-2-6 Fc (Vibration Resistance) 5g @ 10 - 150Hz, Amplitude 0.35mm (Operation/Storage/Transport) IEC60068-2-27 Ea (Shock) 25g @ 11ms (Half-Sine Shock Pulse; Operation) 50g @ 11ms (Half-Sine Shock Pulse; Storage/Transport) IEC60068-2-32 Ed (Free Fall) 1M (3.281ft.)

Order Information

IES-0822 - 4 x 802.3af + 3 FE+ 1 MM SC Unmanaged Switch -40 to 75C, DIN-rail

Package Contents

IES-0822

Quick Installation Guide