




# USB-0401 USB Gigabit Ethernet Adapter



USB-0401


H/W Version: 3

The LevelOne USB Gigabit Ethernet Adapter is a USB adapter that enables desktop and notebook computers with high-speed Gigabit network connectivity via the USB port.

The USB-0401 is USB3.0 as well as IEEE802.3 (10Mbps), 802.3u (100Mbps) and 802.3ab (1000Mbps) compliant, ensuring that users can utilize any networking environment available.

It supports hot inserting and swapping, meaning that the USB-0401 can be installed quick and easy without shutting down the computer or opening up the computer box to install new network interface cards.

With low power consumption and mobility without the need of any additional power cords, notebook computer users greatly benefit from using this network interface adapter.



## Key Features

- Provides an Internet connection through a single USB port
- 10/100/1000Mbps wire speed transmission and reception
- Compatible with USB 3.0 / 2.0 standards
- 4K jumbo frames to increase data transfer rates
- Built-in Wake-on-LAN feature to startup/shutdown computers remotely
- Supports IPv4/IPv6 network operation
- No additional power supply required
- IEEE 802.3x Flow Control protects against lost packets for Minimize carbon footprint with advanced energy efficient technology (IEEE 802.3az)
- Supports Windows XP / Vista / 7 / 8 ; Mac 10.6 / 7 / 8

## Works Well With



**GNS-1001**  
1-Bay Gigabit Network Storage



**WGR-6013**  
300Mbps Wireless Gigabit Router

## Technical Specification

### Interface

USB 3.0 (2.0 Compliant)  
1 x 10/100/1000Mbps RJ-45 port

### Standard

IEEE 802.3: 10Base-T (Ethernet)  
IEEE 802.3u: 100Base-T (Fast Ethernet)  
IEEE 802.3ab: 1000Base-T (Gigabit Ethernet)  
IEEE 802.3x Flow Control (full-duplex flow control)  
IEEE 802.3az Energy Efficient Ethernet

### Data Transfer Rate

Ethernet: 10Mbps (Half/Full Duplex)  
Fast Ethernet: 100Mbps (Half/Full Duplex)  
Gigabit: 1000Mbps (Half/Full Duplex)

### LED Indicator

Green:  
LAN activity, when data is being transferred on the Ethernet network to host system.

Amber:  
On for connection to a 1000Mbps network  
Off for connection to a 100/10Mbps network

### Operating System

Windows XP / Vista / 7 / 8; Mac 10.6 / 7 / 8

### Temperature (°C)

Operating: 10 ~ 40°C  
Storage: 10 ~ 80°C

### Humidity (Non-condensing)

< 85%

### Power Consumption (W)

Operating Mode: 2  
Suspend Mode: 0.19

### Weight (g)

46g


### Dimensions (W x D x H mm)

97 x 23 x 15 mm

### Approval

CE/FCC

## Product Diagram



## Order Information

**USB-0401:** USB-0401 USB Gigabit Ethernet Adapter

## Package Content

USB-0401  
Quick Installation Guide  
CD – User Manual / Utility