

Datasheet_WAB-1000



11g Wireless Outdoor AP/ Bridge

LevelOne's WAB-1000 is a powerful Wireless Outdoor AP that complies with IEEE 802.11 b/g standards and delivers highest speed data up to 54Mbps. Meanwhile, two wireless modules allow the AP to be operated in the AP and Repeater/Bridging modes simultaneously. With weatherproof housing and built-in heater (for WAB-1000H), this device can handle indoor/outdoor applications even in the most rugged operation environments.

Wireless network data is protected with 64/128-bit WEP and AES/3DES encryption, and enhanced with Wi-Fi Protected Access (WPA) and 802.1x user authentication. WAB-1000 also detects rogue access points, further to protect your network from unauthorized access

In order to deploy the installation of the wireless outdoor AP anywhere, WAB-1000 offers a built-in POE function to eliminate power cable and adapter management. With its Web-based management interface, the user can easily configure and maintain the AP through a general browser. Additionally, by using LevelOne's various outdoor antennas, access coverage can be greatly extended.



WAB-1000

Key Features

- Compliant with IEEE 802.11b/g and 802.3 af standards
- Simultaneously operates in AP Mode, Repeater or Bridging Mode,
- Supports strongly wireless security including 64/128-bit WEP, AES/3DES Encryption, WPA, 802.1x
- Supports SNMP v.3 network management
- Supports POE function, eliminating power cable management and cost
- Weatherproof; Rugged for outdoors use
- 1 WAN port; 1 LAN port
- Detects rogue APs
- RF Management for variable power control
- Works with a variety of antennas


Datasheet_WAB-1000




Technical Specification

- **Wireless LAN Standards**
IEEE 802.11b; IEEE 802.11g
- **Frequency**
2.4~2.479MHz
- **Protocol**
CSMA/CA with ACK
- **Antenna**
2 x 5dBi, swivel and dipole Antenna for AP
1 for Bridging
- **Data Rate**
54, 48, 36, 24, 18,12, 9, 6 Mbps
11, 5.5, 2, 1 Mbps
- **Channel Number**
Fix channel
Automatic channel selection
- **Security Support**
64/128-bit WEP
WPA
IEEE 802.1x authentication
AES/3DES for bridging/repeating
Wireless AP activities monitoring
- **Operating Mode**
AP, AP Client, Repeater, Bridging
- **Wired LAN standards**
IEEE 802.3; IEEE 802.3u; IEEE 802.3af
- **Port**
1 x 10/100 Mbps WAN port w/ auto MDIX
1 x 10/100 Mbps LAN port w/ auto MDIX
- **Management**
SNMP v1, v3 agent
- **Ethernet Setting**
Fixed IP/ DHCP Client
Supports 10/100Mbps auto negotiation
- **LEDs**
Power
WAN
WLAN/ WLAN1/ WLAN2
- **Temperature**
Operating WAB-1000A: 0°C~70°C
Operating WAB-1000H: -30°C~70°C
Storage: -40°C~95°C
- **Humidity**
Operating: 20% ~ 80%
- **Dimension**
235mm(L) * 210mm(W) * 78mm(H)
- **EMI and Safety**
FCC Class A, CE

Product Diagram



WAB-1000 Operated in Bridge Mode



WAB-1000 Operated in AP Mode

Ordering Information

- WAB-1000A: 11g Wireless Outdoor AP/ Bridge
- WAB-1000H: 11g Wireless Outdoor AP/ Bridge with Heater