



11g Wireless P/T Network Camera



WCS-2060

H/W Version: 2

LevelOne WCS-2060 is a Pan and Tilt wireless IP network camera. It is able to broadcast live images to your handheld mobile phone or PDA and supports 3GPP/ISMA RTSP format via a 2.5G/3G mobile phone.

Pan/Tilt Network Camera

The WCS-2060 contains a CMOS sensor to record brilliant images up to 640 x 480 pixels. The Auto Pan function allows the user to define individual cameras automatic panning movements thus providing the capability to survey the widest range of targets over a pan range of 350-degrees and a tilt range of 125-degrees. The Patrol mode allows the user to preset up to 20 spots for sequential auto-monitoring.

Remotely, Advanced Monitoring Features

The motion detection feature provides flexibility to record only when there is motion thus saving record storage. With a built-in web server, the WCS-2060 provides remote access to receive video signals from anywhere anytime over the Internet with the Internet Explorer browser.

Easy Maintenance and Configuration

With LevelOne's free bundled software, administrators are able to monitor up to 32 channels simultaneously. For full-featured surveillance solutions to your camera needs, LevelOne WCS-2060 absolutely provides optimum solutions when building a digital surveillance environment.



- 1. LAN Port
- 2. Power Cord Socket

Key Features

- Built-in 1/4" CMOS sensor and high sensitive microphone to deliver high quality streaming video
- Motorized wide-range Pan/Tilt.
- Supports MPEG4 (Short header mode) compression for streaming video and JPEG for still Image
- Supports 3GPP/ISMA RTSP
- Intelligent Motion Detection
- Free software included (Industry-leading 32-channel IP CamSecure Lite™ software)

Works Well With



FCS-9464
IP CamSecure Pro64 Mega




FCS-7011
1-port PoE Video Server

Technical Specification

Network
1 x RJ-45 10/100 Mbps port IEEE 802.11b/g
Wireless Security
64/128-bit WEP; WPA-PSK
Frequency
2.4~ 2.4835GHz
Antenna
Gain Value: 5 dBi RF Output Power: 64QAM: 14dBm; 16QAM: 15dBm; QPSK: 16dBm; BPSK: 17dBm; DBPSK, DQPSK, CCK: 17dBm
Video
Compression Mode
MPEG4 (Simple Profile) for streaming video JPEG for still image
Max. Resolution
640x480 pixels
Frame Rate
Up to 30/25 frames at 160x120 Up to 30/25 frames at 176x144 Up to 30/25 frames at 320x240 Up to 30/25 frames at 640x480 Still Picture JPEG
Video Record
AVI
Camera
Sensor
1/4 inch color CMOS sensor
Lens
4.0mm, F2.0
View Angle
Vertical 37° Horizontal 49°
Minimum Illumination
1Lux/ F2.0
Electronic Shutter (Sec)
1/60 to 1/15,000 sec
AGC/AWB/AES
Audio
Audio In
Omni-directional microphone Frequency: 50 – 16,000Hz
Audio Codec
GSM-AMR/ MPEG4 AAC
S/N Ratio
>60dB

PTZ
Pan
350° (+175°~-175°)
Tilt
125° (+90°~-35°)
Number of preset positions
20
Digital Zoom
4x
Hardware & Environment
Flash ROM
4MB Flash ROM
SDRAM
32MB SDRAM
Housing
Indoor use
Power
12VDC,1.5A
Temperature
Operating: 0°C -40°C (32°F -102°F)
Humidity
Operating: 85% (RH)
Dimension
121.4mm(L) * 110mm(W) * 103mm(H)
Weight
222g
LEDs
System power and status indicator System activity and Network link indicator Microphone status indicator
Supported Protocols
UPnP, TCP/IP, RTSP/RTP/RTCP, HTTP, SMTP, FTP, Telnet, NTP, DNS, DHCP, DDNS and PPPoE
Software
Bundled with 32-Channel LevelOne IP CamSecure Lite surveillance management software
Viewing System Requirement
OS
Microsoft Windows 2000/XP/Vista
Browser
IE 6.x or above, Firefox, Safari, Mozilla, Netscape
3GPP Player
Real Player 10.5 or above Quick Time 6.5 or above
EMI and Safety
FCC, CE

Product Diagram



Order Information

Package Contents

WCS-2060: 11g Wireless P/T Network Camera

WCS-2060

Power Adapter

Dipole Antennas

Mounting Kit & Pads

CD Manual/Utility

Quick Installation Guide