

11g, Wireless Mini Printer Server with One Parallel Port

11g, Wireless One Parallel Port Print Server -- LevelOne WPS-9121 is a Mini-sized printer server that is designed to perform with any stand-alone parallel port printer resource to network users. This unit can support 10/100Mbps wired and IEEE802.11b/g wireless network. Users can share the printer and configure the printer server either through wired or wireless network. WPS-9121 is also equipped with a bi-directional parallel port that instantly attaches to a parallel printer.

Supports Peer-to-Peer and Server-Based Printing --Our LevelOne WPS-9121 supports both Peer-to-Peer and Server-based printing. Peer-to-Peer printing, which allows LAN clients connect directly with the printer server to execute printing functions; and Server-based printing, which allows other customers send print material first to a server which then connect with the printer server to execute printing jobs.

Supports Complete Printing Methods and Major OS-- The WPS-9121 printer server provides LPR, IPP, SMB/TCP, Raw Printing and Unix Logical Printer printing methods. Simply choose the best method according to your environment. This unit is compatible with all major operating systems including Windows™ 98SE/ME/NT/2000/XP, NetWare (3.x above), MAC OS and Unix/Linux environments to provide cross-platform accessibility.

Easy Installation and Configuration-- With its friendly web-based management interface, WPS-9121 is ready for users easily to configure and maintain this device through a general web browser. Clients can immediately utilize any features of this product simply by attaching the cables and turning on the power. The small-sized design will save limited space and thus can be located anywhere on the network.

Fault-Tolerant Firmware Upgrades – Users need not worry about errors occurring in the middle of an upgrade thus preventing the printer server from operating. This unit's fault-tolerant upgrade function allows for re-upgrades should problems occur during the initial upgrade.

With its standard features, the WPS-9121 offers the most exacting network printing solution for any environment from SOHO office to Enterprise thus increasing the productivity and saving costs.



WPS-9121

Related Products



FPS-9021

Mini Printer Server with One Parallel Port



WPS-9121

Mini Printer Server with One USB 2.0 Port



WPS-9122

11g Wireless Mini Printer Server with One USB 2.0 Port

Key Features

- Complies with IEEE 802.3, IEEE 802.3u Wired Ethernet and IEEE 802.11b/g Wireless LAN Standards
- Provides one printer port that can attach directly to a printer's parallel port
- Shares printer to all LAN users
- Supports Peer-to-Peer printing (TCP/IP/IPX/NetBEUI)
- Supports Server-based printing (Novell/Windows)
- Easy to install and setup with Web-based interface
- Supports Fault-tolerant upgrade capability
- Supports Network Protocols: TCP/IP, IPX/SPX, NetBEUI and AppleTalk
- Supports Printing Protocols: LPR, IPP, SMB/TCP, Raw Printing and Unix Logical printing
- Compatible with major Operating System: Windows™ 98SE/ME/2000/XP, Netware (3.x above), Unix/Linux

Technical Specification

Networking

- **Standards Compliance**
 - IEEE 802.3 10BaseT Ethernet
 - IEEE 802.3u 100Base-TX Fast Ethernet
 - IEEE 802.11 b/g
- **Ports**
 - 1 x RJ-45 10/100 Mbps port

Hardware

- **CPU**
 - RISC CPU
- **Flash**
 - 1MB NOR Flash
- **RAM**
 - 8MB SDRAM
- **Printer Port**
 - 1 x Centronic Parallel Port

Print Server Specification

- **Supports Network Protocols**
 - TCP/IP
 - IPX/SPX
 - NetBEUI
 - Apple Talk
- **Supports Printing Protocols**
 - LPR
 - IPPSMB/TCP
 - Raw printing
 - Unix Logical Printing
- **Compatible Operating System**
 - Windows™ 98SE/ME/2000/XP
 - NetWare (2.x Above)
 - MAC OS
 - Unix/ Linux

Wireless Spec

- **Antenna**
 - External 2dBi Dipole Antenna
- **Transmit Output Power**
 - 16dBm~18dBm
- **Frequency Band**
 - 2.4GHz ~ 2.4835GHz


Management

- **Interface**
 - Web-based management Interface
 - Windows Configuration Utility
- **Upgrade**
 - Fault-Tolerant Upgrade capability

Physical Spec

- **LEDs**
 - System power and status indicator
 - System activity and Network link indicator
- **Power**
 - 5 VDC, 1A Power Adapter
- **Temperature**
 - Operating: 0-55°C
- **Humidity**
 - Operating: 10-90% (RH)
- **Dimension**
 - 105mm(L) * 104mm(W) * 125mm(H)
- **Weight**
 - 430g
- **EMI and Safety**
 - FCC, CE

Product Diagram



Ordering Information

- WPS-9121: 11g Wireless Mini Printer Server with One Parallel Port

For more information, please contact your LevelOne representative, or visit our website
 All technical specifications are subject to change without notice.
 All mentioned brand names are registered trademarks and property of their owners
www.level1.com