

LevelOne IP Camera Quick Installation Guide



Quick Installation Guide

This QIG applies to : FCS-1010/1030/1040/1050/1060/1070/3000

WCS-2010/2030/2040/2060/2070

Software Installation

Please insert the CD-ROM that comes with the LevelOne IP camera packet.

The installation page should pop up. If you do not see the pop up, please go into the CD-ROM directory and click on AutoRun.exe

Click on "Install Software".



Click on "Installation Wizard".



Please follow the wizard by clicking "Next".



Click on "Finish" to complete the installation.



Click on the Installation Wizard on your Windows Desktop.



Please choose the IP Camera by MAC address and click "Link to selected device".

Installation Wizard	1				
level Ne	twork Came	ra Configi	uratio	n Levi	
-	MAC Address	IP Address	Assigned	Model	Auto IP
Setup	00-11-6B-80-33-3A	192.168.50.119	Yes	WCS-2060	Yes
Upgrade					
Reset to default					
Exit				_	
About	Search Add	Remove	ncheck All	Link to selecte	d device(s)

Initial login will have a Window pop up, please click "yes".



Install Active X.



Complete installation.



Wireless installation

This applies to WCS-2010/2030/2040/2060/2070

Login to the web configuration page, click on Wireless LAN.



Please press "save" after configuration, and then unplug your power cord and RJ-45 LAN cable. Insert Power cord, do not insert RJ-45 LAN cable. LevelOne IP camera should automatically connect to the preset AP.

Surveillance System QIG

Please insert the CD-ROM that comes with the LevelOne IP camera packet.

The installation page should pop up. If you do not see the pop up, please go into the CD-ROM directory and click on AutoRun.exe.

Click on "Installation Software".

Click on Surveillance Software.

Click "Next".

Click "Yes".

Please input the User Name and Company Name then click on "Next".

nstallShield Wi	zard
Customer Info Please entery	rmation our information.
<u>U</u> ser Name:	
tom	
<u>C</u> ompany Nar	ie:
levelone	
Install this app	lication for:
	C Only for me (Colling)

Please input the Password for accessing the Surveillance software then click on "Next".

InstallShield	Wizard				>
Root Pass v	ord Setup				Z
You must se the following	et root password before ; 3.	you could use t	his program. F	Please type the p	assword in
Password:	*****				
Confirm:	NXMMM				
nstallShield					
ristella nielu			< <u>B</u> ack	<u>N</u> ext>	Cancel

Choose your path of installation, click "Next".

Click on "Next".

stallShield Wizard		
Select Program Folder Please select a program folder.		N2
Setup will add program icons to the Program F name, or select one from the existing folders li Program Folders:	Folder listed below. You may typ st. Click Next to continue.	e a new folder
LevelOne\Surveillance System		
Existing Folders:		
Acrobat FinePrint Mobuy PowerMap3D V7 Winamp WinRAR 附屬應用程式 啟動		
stallShield	< <u>B</u> ack <u>N</u> ext >	Cancel

Click "Next".

InstallShield Wizard		
Start Copying Files Review settings before copying files.		X
Setup has enough information to start co change any settings, click Back. If you copying files.	pying the program files. If you want to are satisfied with the settings, click No	oreview or ext to begin
Current Settings:		
Setup Type: Complete Target Folder E:\Program Files\LevelOne\Surveill User Information Name: tom	ance System\	
Company: levelone		>
InstallShield	< Back Next>	Cancel

Click on "Finish" to complete installation.

Please click on the Monitor for Surveillance System on your Windows Desktop.

Authentication Windows should pop up, please input the Username as "root", the password is the preset during installation.

Authenticatio	n	
Username:	root	
Password:	*****	*
ОК		Cancel

The surveillance window should appear.

If the window does not pop up, please right click on the icon and choose "Monitor".

Click on the icon then choose "Camera Configuration".

Click on "Yes".

Surveillance System	×
Warning! Continuing will force all reco Do you want to continue?	ordings to stop.
(是1) 否则	

Click on "Insert".

Camera Configuration		X
Local Setting	Remote Settings	
Insert Contraction	Please insert new channel by pressing Insert button	2
Enable gotion detect Enable digital input Digital input alert when Eig Lo Enable video loss		
Enable centre alert Recording Settings Name:		
Record 5 secs. after event Media type: • Both Yideo Audio		
Location Information 1NONE 2NONE		
3NONE 4NONE 5NONE		
6NONE 7NONE 8NONE		
9NONE 10NONE 11NONE 12NONE		
12NONE		
16NONE		
Complete		100%

Input the IP address of your LevelOne IP camera, default port is 80 and password then click on "OK".

<u>A</u> ddress:	192.168.50.199	: 80	-
User:	root		
Password:			
	Save Fassword		

Adding the camera.

When the configuration page pops up, the setting is done. Click on "Save".

Click "OK".

Complete.

